
38 528 001 **RAPID SL ELEMENT FOR WC, 1.13 M INSTALLATION HEIGHT**





PRODUCT DESCRIPTION (1/2)


- Colour: chrome
- with flushing cistern GD 2, 6 - 9 l
- for on-the-wall installations or studded walls
- powder coated steel frame, self-supporting
- for dry-cladding, completely pre-assembled
- with fixed connections
- quick adjustment, lockable
- fixing material
- TÜV approved
- 2 WC fixing bolts
- fixing device for ceramic
- WC ceramics with small bearing area (less than 205 mm) require additional accessory 38 779 000
- distance of fixing bolts 180/230 mm
- outlet bend Ø 90 mm
- depth adjustable
- reducer Ø 90/110 mm
- inlet and outlet connecting set
- flushing cistern GD 2, 6 - 9 l, containing following features:
- adjustment ex factory 6l and 3l
- pneumatic discharge valve offering 3 modes of operation: dual flush or start/stop or single flush
- water supply from left/right or back
- low noise (group I acc. to German Noise Specification)
- insulated against condensation
- ½" water supply connection including integrated angle valve and push fit flexible hose union
- no tools required for the installation of the inspection shaft incl. protection during construction phase
- for vertical or horizontal use
- for on-the-wall installation please order wall brackets 38 558 00M (sold separately)

38 528 001 **RAPID SL ELEMENT FOR WC, 1.13 M INSTALLATION HEIGHT**

PRODUCT DESCRIPTION (2/2)

- for mounting of small flush plates please order revision shaft 40 911 000 (sold separately)

38 528 001 **RAPID SL ELEMENT FOR WC, 1.13 M INSTALLATION HEIGHT**



SPARE PARTS, ก้นยายน 2022 – now

1: Threaded bolt (Order-nr. 4276400M)

2: WC inlet and outlet connecting set (Order-nr. 37311K00)

2.1: Basin fastening (Order-nr. 43511SH0)

2.2: Connector (Order-nr. 37119000)

3: PP-outlet bend Ø 90 mm (Order-nr. 42327000)

4: 4" Outlet Adaptor F Rapid Sl (Order-nr. 42242000)

5: Support for outlet bend (Order-nr. 42243000)

6: Inspection shaft (Order-nr. 66791000)

7: Filling valve (Order-nr. 37095000)

7.1: Lever (Order-nr. 43734000)

7.1.1: Ball seal dia. 9x6.8 mm (Order-nr. 4377000M)

7.2: Valve head (Order-nr. 43536000)

7.3: Membrane (Order-nr. 4375800M)

7.4: Screw cap (Order-nr. 43735000)

7.5: Valve float, 5 pcs. (Order-nr. 4379100M)

7.6: Repl. kit f. seal (Order-nr. 43722000)*

8: Support device (Order-nr. 42246000)

9: Tube (Order-nr. 42233000)

9.1: Seat washer (Order-nr. 0319100M)

10: Dual Flush discharge valve AV1 (Order-nr. 42320000)

10.1: Extension for overflow pipe (Order-nr. 42313000)

10.2: pneumatic hose (Order-nr. 42319000)

10.3: Ball seal dia. 9x6.8 mm (Order-nr. 42310000)

11: Valve seat for GD2 (Order-nr. 42315000)

12: Water Connection (Order-nr. 48561000)

13: Retrofit kit for shower toilets Sensia Arena and IGS (Order-nr. 40899000)

14: Set for noise protection (Order-nr. 37131000)*

15: Xtra wall brackets, flexible placing (Order-nr. 38733000)*

16: Extension (Order-nr. 38629000)*

17: Accessory (Order-nr. 38779000)*

18: 4,5 l Adapter for GD2 (Order-nr. 42333000)*

19: Wall union (Order-nr. 3855800M)*

20: Rapid SL connection set for shower WC (Order-nr. 38925000)*

21: Retro-fit set (Order-nr. 38796000)*

* Optional accessories